



Teknisk data modell C15W

Modell C15W	Kildiameter(mm)	Effektiv längd på Wedge (mm)	Splitsavstånd (mm)	Brytkraft (MN)/ton	Slag cylinder (mm)	Hydrauliskt tryck (MPa)	Längd (mm)	Vikt (kg)	Bit diameter (mm)	Borrdjup (mm)
C15W 28A200	28	183	7,5	5,3/540	150	85	923	30	30	360
C15W 30B200	30	183	9	4,4/449	150	85	923	30	32	360
C15W 34D200	34	183	12	3,3/337	150	85	923	30	36	360
C15W 40D300	40	300	12	3,3/337	150	85	1040	30	42	460
C15W 42A450	42	450	7,5	5,3/540	150	85	1190	31	44	610
C15W 42B400	42	400	9	4,4/449	150	85	1040	31	44	560
C15W 42D300	42	300	12	3,3/337	150	85	1040	30	44	460

Teknisk data modell K25W

Modell K25W	Kildiameter(mm)	Effektiv längd på Wedge (mm)	Splitsavstånd (mm)	Brytkraft (MN)/ton	Slag cylinder (mm)	Hydrauliskt tryck (MPa)	Längd (mm)	Vikt (kg)	Bit diameter (mm)	Borrdjup (mm)
K25W 40A400	40	400	12,5	6,5/663	250	85	1343	35	42	660
K25W 42A440	42	440	12,5	6,5/663	250	85	1395	36	45	700
K25W 58D370	58	370	20	4,1/418	250	85	1325	36	60	630
K25W 62A500	62	500	12,5	6,5/663	250	85	1455	37	64	760